

**TECHNICAL  
INFORMATION**

**SeraMark™ Wall Graphic Media - Pressure Sensitive Adhesive Coated**

SeraMark is composed of a printable woven fabric with a repositionable pressure sensitive adhesive. Available grades include top coatings compatible with offset, solvent inkjet, aqueous inkjet and laser printing methods.

SeraMark is the ideal choice for wall graphics, as it has the perfect balance of flexibility for conforming on un-even surfaces and rigidity for superior die-cutting.

**SeraMark - 750**  
Solvent Inkjet

<b>TYPICAL PROPERTIES – Fabric face</b>	<b>UNITS</b>	<b>VALUE</b>	<b>TEST METHOD</b>
Nominal Gauge - Average	Mils	4.2	Continuous Gauging
Yield	Sq.In./Lb	6,099	Approximate
Basis Weight - 25" x 38" x 500	Lbs./MMSI	164	Approximate
	Lbs./Ream	78	
Tear Strength	MD Grams	116	
	CD Grams	160	
Opacity	%	90	
<b>TYPICAL PROPERTIES – Adhesive</b>	<b>UNITS</b>	<b>VALUE</b>	<b>TEST METHOD</b>
Peel Data			
Stainless	Oz/in	13.6	30 min @ 73°F
Tack Data			
Loop Tack	Lbs/sq.in.	0.65	
Probe Tack	Grams	235	
Application Data			
Minimum Application Temperature	Deg. F	35	
Time for Ultimate	Hours	24	
Service Temperature	Deg. F	32 – 150	
Shelf Life	Years	1	

The information contained herein is to the best of our knowledge true and accurate. Nothing contained herein is to be construed as a recommendation to use any product in conflict with any patent. Purchaser should confirm product compatibility prior to use since CONVERT-ALL, INC. MAKES NO WARRANTIES AS TO THE FITNESS OR MERCHANTABILITY OF ANY PRODUCTS REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations, and disclaims all liability for resulting loss or damage.